

BLW=5HP DIRECT DRIVE PADDLE WHEEL BLOWER 1550 CFM @ 6" S.P. CLS=COMMERCIAL DUTY DOOR CLOSER DIS=NON-FUSED DISCONNECT SWITCH FOR CONTROL PANEL EMO=EMERGENCY STOP SWITCH DR1=CLEAR ANODIZED ALUMINUM FRAME DOOR (ENTRY END)
DR2=CLEAR ANODIZED ALUMINUM FRAME DOOR (EXIT END) FL1=99.99% @ .3 MICRON HEPA FILTER FLX=8" DIAMETER FLEX CONNECTION FOR RETURN AIR

GLS=0.25" THICK CLEAR TEMPERED GLASS

GRL=RETURN AIR GRILLE

HNG=4.5" NICKLE PLATED BUTT HINGE

LGT=LED LIGHT FIXTURE

MOT=5HP DIRECT DRIVE OPEN DRIP PROOF MOTOR 3500 RPM NOZ=0.875" DIAMETER WHITE PLASTIC AIR NOZZLE (30 IN WALLS & 6 IN CEILING) PL1=HEPA FILTER PLENUM 0.60" THICK ALUMINUM CONSTRUCTION PL2=RETURN AIR PLENUM 0.60" THICK ALUMINUM CONSTRUCTION

PNL=NEMA 1 ENLOSURE CONTROL PANEL

PRE=MERV 7 PANEL FILTER

SLV=SLEEVED PENETRATION THROUGH ROOF FOR INSTALLTION OF SPRINKER

STP=PEMKO #285CPK DOOR SEALS SWP=PEMKO #307AV DOOR SWEEP

## Notes:

- 1. The control panel is recessed in mechanical wall on entry side of air shower.
- 2. The air shower is shipped knock down into (3) walls, (1) roof and (2) doors.
- 3. The air shower is supplied with a sleeved penetration through the roof section for installation of a sprinkler head. Sprinkler is by others.

  4. The air shower does not have a floor. It uses the existing floor.



PO Box 427 Rancho Cucamonga, CA 91729-0427 Voice: (800) 913-0054 Fax: (909) 483-1801

Drw# LP7248LA MODEL "LP" AIR SHOWER Project: Date: Sheet: